

1.1.2.5 Medium Power Large Aperture Thermal Sensors – Apertures to 120mm

1W to 500W

Features

- Very large aperture
- Pulsed absorber
- Up to 500W
- Ø120mm aperture

L100(500)A-PF-120



Model	L100(500)A-PF-120	
Use	High peak power, high energy measurements	
Absorber Type	PF volume absorber	
Spectral Range μm	0.15 – 20	
Aperture mm	Ø120mm	
Power Mode		
Power Range	1W – 500W	
Maximum Intermittent Power	500W for 2min, 100W continuous, 500W continuous if heat sunked on rear	
Power Scales	500W / 50W	
Power Noise Level	50mW	
Maximum Average Power Density W/cm ²	2000	
Response Time with Meter (0-95%) typ. s	7	
Calibration Uncertainty $\pm\%$	1.9	
Power Accuracy $\pm\%$	4 ^(a)	
Linearity with Power $\pm\%$	2	
Energy Mode		
Energy Range	6J – 6000J	
Energy Scales	6kJ / 600J / 60J	
Minimum Energy	6J	
Maximum Energy Density J/cm ²	Single 10-50Hz ^(b)	
<100ns	3 ^(c) 1.5	
1 μ s	3 ^(c) 1.5	
0.5ms	7 7	
2ms	15 15	
10ms	40 40	
1s	3000 NA	
Cooling	Convection or conduction	
Fiber Adapters	Consult Ophir representative	
Accessories for High Power Sensors	See pages 113-116	
Weight kg	4.4	
Compliance	CE, UKCA, China RoHS	
Version		
Part number	7Z02765	
Notes: (a)	Calibrated for 0.25 – 2 μm	
Notes: (b)	For 10-50Hz derate as follows: 1064nm not derated 532nm not derated 355nm 70% of stated value 266nm 15% of stated value 193nm 10% of stated value	
Notes: (c)	Damage threshold 1.5J/cm ² for wavelengths <500nm	

* For drawings please see page 73

L100(500)A-PF-120

