

1.1.2.7 High Power Thermal Sensors

1.1.2.7.3 High Power Water Cooled Thermal Sensors

100W to 20kW

Features

- High powers
- Water cooled
- Up to 20kW
- Up to Ø55mm apertures
- Over temperature alarm and interlock

15K-W-BB-45



20K-W-BB-55



Model	15K-W-BB-45	20K-W-BB-55		
Use	High power up to 15kW	High power up to 20kW, larger aperture, over temperature alarm and interlock		
Absorber Type	Beam deflector + broadband absorber	Beam deflector + broadband absorber		
Spectral Range μm ^(a)	0.8 - 2, 10.6	0.8 - 2, 10.6		
Aperture mm	Ø45mm	Ø55mm		
Power Range	100W - 15kW	100W - 20kW ^(f)		
Power Scales	15kW / 4kW / 400W	20kW / 5kW / 500W		
Power Noise Level	1W	1W		
Backscattered Power ^(b, e)	~3.5% without Scatter Shield, ~1% with Scatter Shield	~3.5% without Scatter Shield, ~1% with Scatter Shield		
Maximum Average Power Density kW/cm ²	See note ^(c) and table ⁽ⁱ⁾ below	See note ^(c) and table ⁽ⁱ⁾ below		
Response Time with Meter (0-95%) typ. s	3.5	3.5		
Calibration Uncertainty $\pm\%$	1.9	1.9		
Power Accuracy $\pm\%$	5 ^(a)	5 ^(a)		
Linearity with Power $\pm\%$	2	2		
Variation with Beam Size	$\pm 1.7\%$ from 15 to 30mm	$\pm 1\%$ from 10 to 35mm		
Cooling	water ^(d)	water ^(d)		
Minimum Water Flow Rate	12 liter/min at full power ^(d)	20 liter/min at full power ^(d)		
Water Pressure Requirements at Max Flow Rate	Pressure drop across sensor ~0.2MPa	Pressure drop across sensor at full flow rate <0.1MPa		
Water Connectors ^(e)	Quick connector for 3/8" OD nylon tubing	Quick connector for 1/2" OD nylon tubing		
Over Temperature Warning / Interlock	N.A.	Module on sensor near output cable with over temperature LED, loud audible signal and M8 3 connector interlock		
Cable Length and Connections	5 meters terminated in Ophir DB15 smart connector	Signal: 5 meters terminated in DB15 Interlock: M8 connector with 1.5 meter cable terminated in flying leads: Brown - common, Black - N.C., Blue - N.O.		
Optional Scatter Shield Accessory ^(e)	10K-W / 15K-W Scatter Shield (P/N 7Z08295)	20K-W Scatter Shield (P/N 7Z08355) ^(g)		
Weight kg	6	8		
Compliance	CE, UKCA, China RoHS	CE, UKCA, China RoHS		
Version	V2			
Part number	7Z07133	7Z07149		
Note: (a)	Calibrated at 1.07 μm and 10.6 μm . For other wavelengths in the ranges of 0.8 - 0.95 μm & 1.1 - 2 μm , the calibration error may be up to $\pm 2\%$ more.			
Note: (b)		When scatter shield is installed, use the NIRS setting to compensate for slightly higher reading. When not installed, use the NIR setting.		
Note: (c)		For circular beam centered within 1/4 of beam diameter. IMPROPERLY CENTERED BEAM CAN CAUSE DAMAGE TO SENSOR.		
Note: (d)		Maximum tilt angle ± 5 degrees. For rectangular beam, please consult Ophir representative.		
Note: (e)		Water temperature range 18-30°C. Water temperature rate of change $<1^\circ\text{C}/\text{min}$. The recommended flow rate can be lowered proportionately at lower than full power but should not be below 3 liter/min. The response time will be optimum at near 12 liter/min flow rate. For solutions for prolonged usage with untreated water (tap water, non DI water), please contact Ophir.		
Note: (f)		For further information and other options see Accessories for High Power Sensors on pages 113-116.		
Note: (g)		With scatter shield full power is 18kW.		
Table: (1)	The scatter shield is compatible also with the 16K-W-BB-55 sensor P/N 7Z07131			
	Beam diameter	Max power density	Max energy density	
		1ms pulse width	3ms pulse width	10ms pulse width
<15mm	10kW/cm ²	30J/cm ²	60J/cm ²	150J/cm ²
15 - 20mm	7kW/cm ²	20J/cm ²	40J/cm ²	100J/cm ²
20 - 40mm	5kW/cm ²	15J/cm ²	30J/cm ²	70J/cm ²
40 - 45mm	4kW/cm ²	12J/cm ²	25J/cm ²	60J/cm ²

15K-W-BB-45

