


SupIR 7.5mm f/1.2, Fixed Athermalized 680331



HD
FORMAT



HFOV	320x240	384x288	640x480	1024x768
17 μ	42.5°	51.4°	90.9°	
12 μ	29.7°	35.8°	61.1°	106.5°

Property	Value				
Optical					
Focal Length	7.5mm				
F#	1.2				
Average transmission (8-12 μ m)	93% (HD) / 87% (HC)				
Back Focal Length	12.8mm in air				
Mechanical					
Focus Mechanism	Fixed				
Depth of Field	2m to infinity				
Focus Range	0.4m to infinity				
Weight	see configurations table below				
Max. Dimensions	see configurations table below				
Environmental					
Operation Temperature	-40°C to +80°C				
Storage Temperature	-50°C to +85°C				
Sealing	IP 67 front element only				
Configurations	Weight (gr)	Dimensions	BWD**	Thread	Coating
680331-001					HD
680331-002	24.5	Ø25.12mm x 18.8mm		M24x0.5	LRHC***
680331-007			9.7		HC
680331-005				M34x0.5	HD
680331-006	43.9	Ø34.9mm x 18.8mm			LRHC***

* The ICD drawing provided here is primarily a representation and may not accurately reflect the product's actual dimensions and specifications. For precise integration specifications contact your local sales representative.

** The BWD value is calculated for a unique detector setup with varying sealing windows in terms of thickness and material. For more details, contact your local sales representative.

*** For detailed LRHC coating specifications see page 13